

A blue electric hoist is shown, featuring a blue motor and a blue frame. A red hook is attached to the bottom of the hoist, and a red label with the text "1000kg" is visible on the hook. The hoist is mounted on a blue beam.

Capacity (T)	Working ruler	Lifting Height (M)	Lifting speed (M/Min)	Running Speed (M/Min)	Pulley No.	Lifting Motor Model & power(kw)	Running motor Model & power(kw)	Levels of protection	I-Beam Track Model	Min Radius	Weight
1	M3	6	8 8/0.8	20 20/6.7 30 30/10	2/1	ZD22- 4(1.5) ZDSI- 0.2/1.5 (0.2/1.5)	ZDY11- 4(0.2)	IP44 IP54	116a ~ 128b	1	180
		9								1	190
		12								1.2	205
		18								1.8	220
		24								2.5	235
		30								3.2	255
2	M3	6	8 8/0.8	20 20/6.7 30 30/10	2/1	ZD31-4 (4.5) ZDSI-0.4 (0.4/3)	ZDY12- 4(0.4)	IP44 IP54	120a ~ 145c	1.2	250
		9								1.2	265
		12								1.5	300
		18								2	320
		24								2.8	340
		30								3.5	360
3	M3	6	8 8/0.8	20 20/6.7 30 30/10	2/1	ZD32-4 (4.5) ZDSI- 0.4/4.5 (0.4/4.5)	ZDY12- 4(0.4)	IP44 IP54	120a ~ 145c	1.2	320
		9								1.2	340
		12								1.5	350
		18								2	380
		24								2.8	410
		30								3.5	440